

**Energy
Storage**

5kW

HYBRID **All NEW Solis Series**

Hybrid Energy Storage Inverter

- ▶ All NEW Intelligent Hybrid PV Inverter
- ▶ Dual MPPT – 3K, 3.6K, 5K
- ▶ Off-grid backup function
- ▶ Export Control
- ▶ UPS function
- ▶ Intelligent EMS function
- ▶ Integrated BMS
- ▶ Smart battery SOC detection - Compatible with various 48V batteries
- ▶ Numerous protection functions
- ▶ CAN, RS485, WiFi/LAN/GPRS (Optional)
- ▶ 5 years standard warranty, 20 years optional upgrade



Model:

RHI-5K-48ES

Features:

**Off-Grid
Backup**

**Flexible
adaptation**
Lithium
battery

**Smart
Energy
management**

7"
LCD

WiFi/GPRS
Real time
monitoring

**Available on the iPhone
App Store**
 **Available on the iPhone
App Store**

Datasheet

Model	RHI-5K-48ES
Energy Control	Inteligent Hybrid with Grid Backup
Input DC(PV side)	
The max DC input voltage(V)	600
Start-up DC voltage(V)	120
MPPT operating voltage range(V)	90-520
MPPT Number	2
The rating max dc input current(A/B)	11A/11A
Battery	
Battery Type	Li-ion
Battery Voltage range(V)	42-58
Battery Capacity(Ah)	50-2000
Maximum Charging Power(W)	3000
Maximum Charging/discharge current(A)	62.5
Output AC(Back-up)	
Rating output power(kW)	3
Transient max. apparent output power	4000kVA, 10sec
Back-up switch time	<10ms
Operation phase	L-N-PE
Rating grid voltage(V)	220/230/240
Rating grid frequency(Hz)	50/60
Rating grid output current(A)	13
THDi	2%(linear load)
Output AC(Grid side)	
Rating output power(kW)	5 (4.6 for 4105)
Max. apparent power from grid(kVA)	5.5
Operation phase	L-N-PE
Rating grid voltage(V)	220/230/240
The grid voltage range(V)	180-270
Rating grid frequency(Hz)	50/60
AC grid frequency range(Hz)	47-52 or 57-62
Rating grid output current(A)	21.7
Output power factor	1 (default) and 0.8leading ... 0.8lagging adjustable
THD	<2%
Efficiency	
Max efficiency of Solar Inverting	>97.5%
European efficiency of Solar Inverting	>96.8%
Max efficiency of Battery Inverting	>95%
Max efficiency of Battery charging	>95%
Protection device	
Ground fault monitoring	Integrated
Residual current mornitoring unit	Integrated
DC AFCI	Optional
DC reverse polarity protection	Yes
Protection class/Over voltage category	I/IV
General Data	
Dimensions(W/H/D)	333*505*249(mm)
Weight(kg)	17
Operation temperature range	-25°C ~ 60°C
Protection degree	IP65
Inverter Topology	High frequency insolation (for battery)
Noise emission (typical)	<20dBA
Cooling concept	Natural convection
Design lifetime	>20 years
Safty/EMC standard	IEC62040-1, IEC62109-1/-2, AS3100, , NB/T 32004, EN61000-6-1, EN61000-6-3
AC and DC Connections	Quick Connection
Interface	CAN/RS485/WiFi/GPRS (optional)
Warranty	5 years standard (extend to 20 years)